

Portable Charging Set 0 - 420 Bar

General:

The Quality Hydraulic Power (QHP) charging and testing unit QCS is used for the charging of Accumulators with Nitrogen gas as well as pressure checking and adjustment.

Section 4 (Commissioning) and Section 4.1 (Pre-Charging Procedure) of 'Instruction Manual for Bladder Accumulators' and 'Instruction Manual for Piston Accumulator' MUST be followed when using the QHP Portable Charging Set.

Technical Specification:

- Suitable for pressures up to 420 Bar
- 5/8" & 7/8" UNF Gas adaptors available upon request

Assembly Inclusions:

- Charging Body
- 2.5 metre hose with 1/4" BSP female connections
- Gauge with a range to suit
- Bull nose adapter for connection to gas bottle (5/8" BSP)
- Bottle key for Nitrogen bottle

Gauges:

- Dual scale as standard in Bar & PSI
- Standard range available as ex-stock



Model No.	Pressure Gauge Range (Bar)
QCS33-1425/A	0-70
QCS33-1425/B	0-140
QCS33-1425/C	0-210
QCS33-1425/D	0-280
QCS33-1425/E	0-350
QCS33-1425/F	0-420

BESPOKE GAUGES AVAILABLE UPON REQUEST

CONTACT QHP LTD FOR MORE INFORMATION:

T: +44 (0) 1244 393500 | E: info@qhp.co.uk | W: www.qhp.co.uk